



## **PARAGON<sup>®</sup>**

### **SHAMPOO UNITS**

### **MODEL 805-BKW**

Before installing and using this unit, please carefully read all instructions. Be sure to keep instructions available for later reference.

**LITERATURE DIMENSIONS ARE FOR GENERAL REFERENCE USE ONLY. INSTALLATION DIMENSIONS SHOULD BE TAKEN DIRECTLY FROM THE SINK. GARFIELD RECOMMENDS THAT A LICENSED PLUMBER PLAN & PERFORM INSTALLATION**

#### **BEFORE YOU BEGIN**

- ☐ Unpack the new sink and inspect for damage. Return the sink to the carton prior to/ during installation.
- ☐ Shut off the hot and cold water supplies.
- ☐ Remove rings, wristwatches and other items that may accidentally scratch or damage the fiberglass surface during installation.
- ☐ Observe local plumbing codes\*

\*GARFIELD RECOMMENDS THAT A LICENSED PLUMBER PLAN & PERFORM INSTALLATION. ALL WORK MUST MEET LOCAL PLUMBING STANDARDS. CHECK WITH YOUR LOCAL PLUMBING INSPECTOR PRIOR TO STARTING ANY PLUMBING WORK. GARFIELD IS NOT RESPONSIBLE FOR INCLUDING LOCAL PLUMBING CODES WITHIN THIS GUIDE. IT IS THE RESPONSIBILITY OF THE PURCHASER AND/ OR THE INSTALLER TO ENSURE THAT THE BOWLS AND ITS' INSTALLATION CONFORMS TO ALL LOCAL PLUMBING CODES.

#### **WARRANTY**

Any alterations, addition, or deletion made to the sink will void the warranty.

#### **CARE & CLEANING**

Keep your sink product looking new by rinsing it thoroughly after each use.

Because of the detrimental effects that mineral deposits, soap scum, and hard water stains have on finished surfaces, it is important to keep your sink and the fixtures clean on a regular basis.

Use the recommended information described in this section. Use of other cleaning materials and/or methods may harm your sink and will void the warranty. Failure to perform periodic maintenance on your sink may cause health and/or safety problems, also possibly harming the bathtub, pump, or piping, voiding all warranties.

Do not use wire brushes, metal sponges, knives, steel wool, or scouring pads on any part of the sink.

Do not use abrasive cleaners or solvents including but not limited to petroleum based solvents such as paint thinner, acetone or abrasive cleanser on any part of the sink.

We recommend that, once a week, wash all exposed surfaces of the sink with a mild solution of vinegar and water. Check for stubborn spots. Oily or greasy spots can be lifted with denatured alcohol. Wipe off with clean warm water until dry.

# **GI** ROUGHING-IN

DO NOT USE ANY PORTION OF THE PLUMBING FOR LIFTING OR POSITIONING THE SINK. THIS UNIT MUST BE FASTENED TO THE FLOOR. PLUMBING FIXTURES ALONE ARE INSUFFICIENT IN SAFELY HOLDING THE UNIT SECURELY IN PLACE.

FLOOR CLEATS AND SPECIAL FASTENERS MAY BE NECESSARY FOR THE PROPER INSTALLATION OF THE SHAMPOO UNITS. BECAUSE EACH SALON AND CONSTRUCTION PROCESS IS DIFFERENT, WE SUGGEST THAT THESE BE OBTAINED LOCALLY BY THE INSTALLER.

LITERATURE DIMENSIONS ARE FOR GENERAL REFERENCE USE ONLY. INSTALLATION DIMENSIONS SHOULD BE TAKEN DIRECTLY FROM THE SINK. GARFIELD RECOMMENDS THAT A LICENSED PLUMBER PLAN & PERFORM INSTALLATION

\*TILTING BOWL MAY REQUIRE USE OF A PVC FLEX PIPE.



