

HiLo MultiPro

Top design Four-piece adjustable top with round corners, three-layer foam, 3/4" plywood

Standard size top 30" x 73"

Foam 2" firm bottom layer + 1- 3/4" medium-density layer of urethane polymer

Polyester batting 1/2" fluffy polyester Dacron top layer

Frame 3/4" plywood frame reinforced for arm rests and face cradle

Adjustments Manual, paddle-release adjustment of knee and upper-body sections

Back tilt angle 0 to 80° Knee tilt angle 0 to 30°



Carbon steel base Sleek, contemporary design with white powder-coat finish

8" leg recess 8" recess from ends of table

Height range - standard 19" to 34" infinite motorized adjustment

Weight capacity Lifting weight capacity 450 lbs.; static weight capacity 500 lbs.

MOTORS & CONTROLS:

Base lift motor One 24v DC, 5 amp max motor/actuator, UL recognized, powered through a

110v, 5 amp transformer

Controls Foot control for lift motor

VINYL:

UltraSoft-Touch - standard Lightly textured, super-soft PU vinyl, fabric backed

OPTIONAL ACCESSORIES:

Armrests Flex Armrests
Face support Contour FaceSpace

Foot extension Salon Footrest or Full Footrest

Neck Bolster Facial Neck Bolster

GUARANTEES:

Structure 10 yr. on replacement parts for frame/structure and 1 yr. on labor**

Motor & controls 2 yr. warranty on materials for mechanical/electrical parts


Vinyl & foam 2 yrs. on materials


**Labor warranty for USA customers only


WEIGHTS:


Table weight 210 lbs. Shipping weight - boxed 250 lbs.

Snipping weight - boxed 250









10/20/2016