

HiLo PowerTilt

(Shown with optional accessories)

TOP:

Top design Four-piece adjustable top with round corners, three-layer foam, 3/4" plywood

Standard size top 30" x 73"

Foam 2" firm bottom layer + 1- 3/4" medium-density layer of urethane polymer

Polyester batting 1/2" fluffy polyester Dacron top layer

Frame 3/4" plywood frame reinforced for arm rests and face cradle

Adjustments Motorized adjustment of height from 19" to 34"

Motorized adjustments of knee, and upper-body sections

Back tilt angle 0 to 60° Knee tilt angle 0 to 30°



Carbon steel base Sleek, contemporary design with white powder-coat finish

8" leg recess 8" recess from ends of table

Height range - standard 19" to 34" (infinite motorized adjustment)

Weight capacity Lifting weight capacity 450 lbs.; static weight capacity 500 lbs.

MOTORS & CONTROLS:

PowerTilt motors Two 24v DC, 5 amp max motor/actuators, UL recognized;

powered through a 110v, 5 amp transformer

Main lift mechanism One 24v DC, 5 amp max motor/actuator, UL recognized

(uses the same transformer as the top motor/actuators)

Controls Hand control

VINYL:

UltraSoft-Touch - standard Lightly textured, super-soft PU vinyl, fabric backed

Vinyl color choices Almond, Camel, Black or White

OPTIONAL ACCESSORIES:

Armrests Flex Armrests
Face support Contour FaceSpace

Foot extension Salon Footrest or Full Footrest

Neck bolster Facial Neck Bolster

GUARANTEES:

Structure 10 yr. on replacement parts for frame/structure and 1 yr. on labor**

Motor & controls 2 yr. warranty on materials for mechanical/electrical parts

Vinyl & foam 2 yrs. on materials

**Labor warranty for USA customers only

WEIGHTS:

Table weight 210 lbs. Shipping weight - boxed 275 lbs.

Rev 10/16







